



Enorossi Sickel Bar Mower

Ideal for small farms. Built to adapt to any type of land. The double action cutter bar ensures a sharp, clean cut on any type of grass. The safety breakaway bar helps protect the cutter from obstructions in the field.

The high speed cutting systems ensure a clean cut by the product. The sickle bar mowers have an allowable cut from -45° to $+45^{\circ}$, respect to the horizontal plan, to allow the mowing of hedges, ditches, banks, etc. The double action cutter bar ensures a sharp clean cut on any type of grass. Three point hitch with double action cutter bar. All bars are equipped with an automatic safety release to protect the bar from any obstacles. The compactness of the sickle bar mower allows working with low-power tractors, ensuring cost saving as well as productivity.

Standard production equipment: cardan shaft, spare blade and blade protection.



FEATURES:

- Frame and 3-point hitch made of FE 510 steel.
- Transmission via three groove pulleys made of spheroidal cast iron with n. 3 belts.
- Drive shaft made of tempered and highly resistant 39NiCrMo3.
- Self-sharpening blade with riveted sections made of high quality steel.
- External shoe made of spheroidal cast iron.
- Main cutter bar made of 55Si7 to ensure high resistance and optimal flexibility.
- Automatic safety release to protect the bar from any obstacles.
- 1080 movements at 540 rpm. Breakaway system.
- Forged support.
- Cuts at -45° up and 45° down.
- High quality powder-coat paint.
- BFS equipped with bolted guards.
- Heavy duty shielded P.T.O shaft.

Model	Cutting Action	Lift	HP	Working Width (Cm)	Weight (kg)
BFS165	Double	MECH/HYD	20-75	165	263
BFS180	Double	MECH/HYD	30-75	180	271
BFS210	Double	MECH/HYD	30-75	210	287