



JF Spin 3000 S2

JF Spin 3000 S2 rake and tedder combo has a flexible system resulting in versatility in a single piece of equipment. Its tines are adjustable and spread the forage evenly for a quicker and homogeneous drying, making the hay process easier and faster.

The change to rake mode is simple and quick where JF Spin 3000 S2 will swath all the dry forage into uniform windrows, improving the baler performance and feeding process afterwards.

ADVANTAGES, FEATURES AND BENEFITS

- Uniform tedding and windrowing due to the adjustable spring system in the horizontal position;
- Safety system locks the rake when on hanging position;
- Standard tedding adjustment with the setting of tires height and rotor inclination.

SPECIFICATIONS:

3-point linkage	Category I & II
Maximum capacity	3 ha/h
Recommended revolution at PTO	350 to 540 RPM
Required power at PTO	15 hp
Tires	15 x 6.00 - 6 A PR
Transport width	2.800 mm
Weight	300 kg
Width for double windrow	6.000 mm (3 turns)
Width for single windrow	3.000 mm
Working width	3.000 mm

*The productivities are average evaluations obtained during test conditions and may vary according to the product humidity degree, specific weight and working conditions.

Model	Raking Width Up To:	Tedding Width Up To:	Weight:	No Arms	No Teeth
DR 420 4R	370/420 cm	340/360 cm	500 kg	12 + 6	24 + 18