



Staalmeester SM 24 Hammer Mill

The SM 24 is equipped with a single cyclone for two bags or a double cyclone for four bags. The cyclone can be removed and a chute can be fitted. This hammer mill has a very powerful blower system that allows the material to be discharged up to 8 m high.

The SM 24 comes with a unique bottom drop that allows the user to discharge the material into an auger system for pelletising or any other similar application. The bottom drop feature also allows the user to mill “wet” material for example, beetroot, sugarcane, forage and much more.

FEATURES:

The auger is equipped with heavy-duty “shredders” that allow the material to be shredded before being milled. Any type of grass and grain types can be fed into the hammer mill. The large infeed tray allows the farmer to place whole square bales into the hammer mill without using labour to take the bale apart. The SM 24 has 16 hardened hammers. The bearings are situated on the outside of the hammer mill which makes for easy bearing replacement and increases the lifespan of the bearings.

POWER OPTIONS AVAILABLE:

Electric 22 kW.
Without motor.
P.T.O. driven on Wheels option



Rotor Ø	865 mm
Rotor Shaft	60 mm
Housing Width	285 mm
Housing Ø	1105 mm
Milling Sieve	360°
Motor Speed	1470 rpm
Rotor Speed	1640 rpm
kW Required	22–37 kW
Effective Screen area	5700 cm ²
Weight with motor	982 kg
Weight without motor	730 kg